

PRO-Link Hayspears



P: 855-361-5987
F: 855-818-8865
sales@pro-link.us

PRO-Link Hayspears

are among the best quality bale spears in the world. This fluted line of 1.625" spears offers the highest capacity rating for a fluted tine in the industry. PRO-Link's design has a verified capacity of 3,000lbs @ 30" load center. The fluted spear penetrates the bale with ease while providing optimum strength.

Whether you need a 48, 39, or 33" tine, the nearly universal PRO-Link Hayspear interchanges easily and offers seamless options for the farmer needing to move efficiently between round and square bales. With three different mounts available, crosshole, tapered, and bracketed, our Hayspear has any job covered.

Value pricing makes the Hayspears affordable for everyone that needs hay tines. PRO-Link's customer service is world class and continues to find new ways to support its customers.

PRO-Link Hayspears

- The **PRO-Link Hayspears** Display improves product visibility and sales.
- Each Display is available in either an 11, or a 22 spear variation featuring a 2' X 2' footprint.
- Display enables dealers to easily offer an assortment of product in a clean, compact and safe way.
- Display unit promotes a premier product well known for reliable performance.



Crosshole Hayspears:

- 48SB - 1.625" X 48" crosshole spear, 165BU bracket, 12X3 bolt and locknut, 3,000 lb. capacity.
- 48SB1 - 1.625" X 48" crosshole spear, 155BU bracket w/ gusset, 12X3 bolt and locknut, 3,000 lb. cap.
- 48SS - 1.625" X 48" crosshole spear, 155 sleeve, 12X3 bolt and locknut, 3,000 lb. capacity.
- 39SB - 1.625" X 48" crosshole spear, 165BU bracket, 12X3 bolt and locknut, 3,000 lb. capacity.
- 39SB1 - 1.625" X 48" crosshole spear, 155BU bracket w/ gusset, 12X3 bolt and locknut, 3,000 lb. cap.
- 39SS - 1.625" X 48" crosshole spear, 155 sleeve, 12X3 bolt and locknut, 3,000 lb. capacity.
- 33SS - 1.625" X 48" crosshole spear, 155 sleeve, 12X3 bolt and locknut, 3,000 lb. capacity.

Tapered Hayspears:

- 48TS - 1.625" X 48" tapered hayspear, 114T sleeve, M30 nut, 3,000 lb. capacity.
- 39TS - 1.625" X 48" tapered hayspear, 114T sleeve, M30 nut, 3,000 lb. capacity.
- 33TS - 1.625" X 48" tapered hayspear, 114T sleeve, M30 nut, 3,000 lb. capacity.

Multi-Purpose Haystix:(Optional)

- 49TXJ - 1.75" X 49" tapered stix, 144T sleeve, M30, JN15 Nuts, 3,500 lb. capacity.
- 436TXJ - 1.375" X 43" tapered stix, 110T sleeve, M24, JN12 Nuts, 1,700 lb. capacity.
- 396TXJ - 1.375" X 39" tapered stix, 110T sleeve, M24, JN12 Nuts, 1,700 lb. capacity.
- 336TXJ - 1.375" X 33" tapered stix, 110T sleeve, M24, JN12 Nuts, 1,700 lb. capacity.

Hardware:

- | | |
|---|---|
| 165BU - 1.625" ID Square Bracket w/ 3" Ubolts | 155BU - 1.625" ID Gusseted Bracket w/ 3" Ubolts |
| 114T - 1.625" ID X 4.75" Tapered sleeve | 112 - 1.625" ID X 2" OD X 4.25" bushing |
| 155 - 1.625" ID X 6" Crosshole sleeve | M30 - Conical nut 30 X 2.0 Metric |
| Stab1 - Stabilizer Assembly w/ spear, sleeve and bolt | 58X3U - .625 X 3" Ubolt Assembly |

